

# TIGER Neo

## 48HL4M-DB

### 450-475 Watt

ALL BLACK MONO-FACIAL MODULE WITH DUAL GLASS

### N-type



### N-type Technology

N-type modules with Tunnel Oxide Passivating Contacts (TOPCon) technology offer lower LID/LeTID degradation and better low light performance.



### HOT 3.0 Technology

N-type modules with JinkoSolar's HOT 3.0 technology offer better reliability and efficiency.



### Durability Against Extreme Environment

High salt mist and ammonia resistance.



### Mechanical Load Enhanced

Certified to withstand:  
6000 Pa front side max static test load  
4000 Pa rear side max static test load




### SMBB Technology

Better light trapping and current collection to improve module power output and reliability.



### Anti-PID Guarantee

Minimizes the chance of degradation caused by PID phenomena through optimization of cell production technology and material control.



<b>25</b> Year Product Warranty	<b>30</b> Year Linear Power Warranty	<b>1</b> % First-year Degradation	<b>0.40</b> % Annual Degradation Over 30 Years
------------------------------------	---	--------------------------------------	---

- IEC61215:2021 / IEC61730:2023
- IEC61701 / IEC62716 / IEC60068 / IEC62804
- ISO9001:2015: Quality Management System
- ISO14001:2015: Environment Management System
- ISO45001:2018: Occupational health and safety management systems



**JKM450-475N-48HL4M-DB-Z2-EU**

# 48HL4M-DB 450-475 Watt

## Mechanical Characteristics

Cell Type	N- type Mono-crystalline
No. of cells	96 (48×2)
Dimensions	1762×1134×30 mm
Weight	24.0 kg
Front Glass	2.0 mm, Anti-reflection Coating
Back Glass	2.0 mm, Heat Strengthened Glass
Frame	Anodized Aluminium Alloy
Junction Box	IP68 Rated
Protection Class	Class II
IEC Fire Type	Class C
Connector Type	JK03M/JK03M2/Others*
Output Cables (Including Connector)	4.0 mm <sup>2</sup> (+): 400 mm , (-): 200 mm or Customized Length

\* MC4 and MC4-EVO2 available upon request and subject to availability

## Packaging Configuration

Pallet Dimensions	1792×1140×1249 mm
Packing Detail (Two pallets = One stack)	37 pcs/pallets, 74 pcs/stack, 962 pcs/ 40'HQ Container

## Specifications (STC)


Maximum Power - P <sub>max</sub> [Wp]	450	455	460	465	470	475
Maximum Power Voltage - V <sub>mp</sub> [V]	30.25	30.48	30.71	30.94	31.17	31.40
Maximum Power Current - I <sub>mp</sub> [A]	14.88	14.93	14.98	15.03	15.08	15.13
Open-circuit Voltage - V <sub>oc</sub> [V]	36.04	36.21	36.38	36.55	36.72	36.89
Short-circuit Current - I <sub>sc</sub> [A]	15.76	15.81	15.86	15.91	15.96	16.01
Module Efficiency STC [%]	22.52	22.77	23.02	23.27	23.52	23.77
Power Sorting	0 ~ +3 %					
Temperature Coefficient of P <sub>max</sub>	-0.29 %/°C					
Temperature Coefficient of V <sub>oc</sub>	-0.25 %/°C					
Temperature Coefficient of I <sub>sc</sub>	0.045 %/°C					

STC: Irradiance 1000W/m<sup>2</sup>, Cell Temperature 25°C, AM=1.5

## Application Conditions

Operating Temperature	-40 °C ~ +70 °C
Maximum System Voltage	1500 VDC (IEC)
Maximum Series Fuse Rating	30 A

## Engineering Drawings



\*Note: For specific dimensions and tolerance ranges, please refer to the corresponding detailed module drawings.

## Electrical Performance

